



#### CONSTRUCTION NOTES:

- 1) THE BLADE IS FULL TANG CONSTRUCTION -- MILD STEEL, ALUMINUM OR OTHER SUITABLE MATERIAL -- BLADE SHOULD VARY BETWEEN 3/16" TO 1/4" THICK (1/8" MIN. THICKNESS).
- 2) THE BLADE HAS A 5/8" WIDE CONVEX GRIND CUTTING EDGE RUNNING THE FULL LENGTH -- THERE ARE FIVE (5) CROSS-DRILLED HOLES IN THE BLADE -- FOUR 1/2" HOLES AND ONE CENTER 9/16" HOLE.
- 2) THE OPTIONAL SCALES ARE TO BE CONSTRUCTED OF WOOD, PLASTIC OR OTHER SUITABLE MATERIAL -- FASTENED WITH THREE (3) 1/8" DIA. RIVETS OR BOLTS -- CROSS-SECTIONAL THICKNESS CAN VARY FROM 1/2" TO 1".
- 3) THE OPTIONAL SCALES ARE WRAPPED WITH CROSS-WEAVED LEATHER THONG/ CORDING -- POMMEL AND END BOLSTER/ CROSS GUARD ARE TO BE MADE OF BUILT-UP LEATHER WRAPPING -- HANDLE CAN BE SEALED WITH WAX, OR OILED.
- 4) GHOSTSOLDIER ASSUMES NO RESPONSIBILITY FOR THE USE (OR MISUSE) OF THIS WEAPON AFTER CONSTRUCTION...IF YOU CUT YOUR HAND OFF (OR ANY OTHER BODY PART), IT'S YOUR PROBLEM!
- 5) THIS PLAN IS OFFERED FOR ENTERTAINMENT PURPOSES ONLY, AND COPYRIGHT OF THIS BLADE DESIGN IS PER THE PERSPECTIVE OWNERS -- IT IS SUBJECT TO REVISIONS AS NEW DATA BECOMES AVAILABLE.

# ELI'S MACHETE v.2.1

# THE BOOK OF ELI

JANUARY 17, 2010  
DRAWN BY:  
GHOSTSOLDIER  
ROBERT DAWKINS © 2010